

HeavyFacer-35-P

HeavyFacer-35-P 는 간단한 작동방법으로 튜브와 파이프 I.D.100-306mm 범위에 사용 할 수 있습니다.

The HeavyFacer-35-P is a combination of power and range in a light and portable design. Rugged and balanced machine suitable for tubes and pipes in the size range of 100mm to 306mm in internal diameter.



| HeavyFacer 35-P | | Application Range | STD. Locking Range | Free Speed | Torque | Pneumatic Power | |
|-----------------|-------|-------------------|--------------------------|------------|-----------------------|-----------------|------|
| | | 100-355mm (4-14") | 100-306mm (4-12") | 35RPM | 180Nm | 1.88HP | |
| Air Consumption | 60cfm | Air Pressure | 6Bar(90psi) | Body Size | 700x310x325mm (WXHXL) | Body Weight | 43kg |

FEED SHAFT :

단단한 구조를 가진 샤프트가 안정적인 헤드의 전진(가공)을 가능하게 합니다. High strength, precise machined and hardened feed shaft provides powerful feeding to the assembly which slides over it.

LOCKING JAWS :

내경 100mm - 306mm까지 안정적인 포지셔닝이 가능하고, 수명이 깁니다. Maximum life and secure positioning. Available within the locking range of 100mm to 306mm.

CENTRAL MANDREL :

큰 힘을 들이지 않고 빠르고 정확하게 안전하게 중심축을 잡을 수 있습니다. Expanding mandrel allows fast, accurate and self centering alignment with torque-free operation safety.

TOOL HOLDER :

커터 바이트를 확실하게 고정시켜 작업중 진동의 영향을 덜 받도록 도와줍니다. Holds the cutting tool bits tightly at the desired position. Its robust construction and support to the cutting bits ensure vibration free performance.

BODY :

가볍고 강한압력을 견뎌내는 알루미늄 바디가 고강도의 작업을 가능하게 합니다. Light weight, high pressure cast aluminum body allows continuous operation under the harshest conditions.

